



Type of use

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a good protection against mechanical risks **including cut (cut level 4, as per EN388 European standard)**. Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly, engineering works, collecting, sorting rubbish...

Technical features

- ✓ **Construction:** Seamless knitter liner. Elasticated knitted wrist. Open back (ventilated).
- ✓ **Materials:** 100% Kevlar® fibres. Latex rubber coated palm.
- ✓ **Colour:** yellow/blue.
- ✓ **Gauge:** 10.
- ✓ **Sizes:** 8, 9, 10.
- ✓ **Packing:** - carton of 100 pairs.
- bundle of 10 pairs.

Learn more: www.singer.fr



Advantages

- ✓ ISO9001 system in production.
- ✓ Quality and high resistance of the **Kevlar®** fiber combined with a thick coating of rubber for exceptionnal mechanical results and a strong grip (anti-slip rubber).
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The back of the glove uncoated allowing the hand to breathe. Excellent grip in dry conditions for safe and secure handling.




Conformity

This glove has been tested according to the european standard **EN388: 2003** against mechanical risks (intermediate design).

It complies with **European Directive 89/686/CEE** on Personal Protective Equipment (**PPE**).

EC type examination certificate issued by **SGS**, notified body **n°0120**.

EN388: 2003. Mechanical data. Information on levels	Level 1	Level 2	Level 3	Level 4	Level 5	TKV10LAT Levels obtained	EN388: 2003
Abrasion resistance (number of cycles)	100	500	2000	8000	-	3	 3 4 4 3
Blade cut resistance (indice)	1,2	2,5	5,0	10,0	20,0	4	
Tear resistance (in newtons)	10	25	50	75	-	4	
Puncture resistance (in newtons)	20	60	100	150	-	3	

Your distributor **SINGER® SAFETY**

SINGER®
safety