

Special  
cold**Use<sup>(\*)</sup>**

Thanks to its technical characteristics, this glove is particularly suitable for all main works requiring good dexterity as well as protection against mechanical risks and especially tearing in cold and dry environment: building, public works, green areas, refrigerated storage...

**Technical features**

- ✓ **Construction:** seamless knitted with elasticated wrist and coloured hem.
- ✓ **Fibres :** acrylic (brushed terry).
- ✓ **Gauge :** 10.
- ✓ **Coating:** foam latex (open back, uncoated).
- ✓ **Color :** grey coating, red liner.
- ✓ **Sizes :** 8 to 11.
- ✓ **Packing :** - carton of 100 pairs.  
- polybag of 10 pairs.

Learn more : [www.singer.fr](http://www.singer.fr)Protection  
against  
cold  
**Main advantages**

- ✓ Seamless construction: improves user comfort (will avoid rough points and consequently the risks of reddening or irritation of the skin). Improves dexterity for easy handling of small parts and reduces hand fatigue.
- ✓ The construction of the glove improves the dexterity when handling fine objects, very appreciable in cold environment.
- ✓ Acrylic fibers: acrylic fibers provide warmth and comfort.
- ✓ Wrist knitted with latex for a better elasticity and an excellent fit of the glove on the hand.
- ✓ Protective coating: the latex coating on the palm provides additional protection to the user and offers better grip .
- ✓ The back of the glove uncoated allows to maintain a good ventilation of the hand.

People who are sensitive to latex should avoid contact with this material. Be careful the glove may lose its insulative properties when becomes wet.

**Conformity**


This glove has been tested as per:

- **EN388 : 2016.** Protective gloves against mechanical risks.
- **EN511 : 2006.** Protective gloves against cold.

It complies with **European Directive 89/686/EEC** on Personal Protective Equipment (**PPE**).  
Category II. EC type-examination certification issued by the **CTC**, notified body **n°0075**.

**EN511: 2006****0 1 0**

Convective cold: level 0  
Contact cold : level 1  
Water proofness: level 0

Tests	Levels	<div>EN388: 2016</div> <div></div> <div>1 1 3 1 X</div>	EN388: 2016:	Level 1	Level 2	Level 3	Level 4	Level 5	
Abrasion	Level 1		Abrasion resistance (number of cycles)	100	500	2000	8000	-	
Blade cut	Level 1		Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	
Tear	Level 3		Tear resistance (in Newtons)	10	25	50	75	-	
Perforation	Level 1		Perforation resistance (in Newtons)	20	60	100	150	-	
Cut (as per EN ISO13997)	Level X  (not tested)			Level A	Level B	Level C	Level D	Level E	Level F
			Cut resistance (N) as per EN ISO13997	2	5	10	15	22	30

Your distributor **SINGER® SAFETY**

**SINGER®**  
safety