

CAPSHIELD

Capstone® Ratcheting Shield



PART

CAPSHIELD • • •

- 4 ventilation holes provide excellent airflow.
- Ratcheting faceshield adjust to 3 positions.
- Capstone goggle with removeable faceshield provides full face protection.
- Includes strap and clips allowing the user to add to either of the Capstone 500 Series goggles.
- Polycarbonate shield conforms to user's face, offering increased protection from impact & dust.

GENERAL SPECIFICATION

Shield Thickness: 2.0mm

Weight: 78gm

Shield size vertical: 177.64mm

Shield size horizontal: 195.58mm

Shield size diagonal: 224.24mm

Strap Length: 232-365mm

Overall width (hinge-hinge): 185mm

CAPSHIELD

Capstone® Ratcheting Shield

PACKAGING

Polybag: 1pc

Outer Carton: 50 pcs

COMPONENT	MATERIAL	FEATURES
Shield	Polycarbonate	Full face protection
Security Button	Polycarbonate	Shield secured on goggle; with angle adjustment

PART	LENS MARKING	FRAME MARKING
ECAPSHIELD	N/A	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter

5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s

F: Low energy impact, resists a 6mm, 0.86g at 45 m/s

B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s

A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication

N: Filter with Anti-Fog features

CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard

P: Manufacture Indication

EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact

B: Medium energy impact

BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets

4: Protection against large dust