Standard

AVAILABLE



Preview

Model Line

ENDURANCE CORVARA

Article Protection

81087-061 S3 SRC

Sole



Working Enviroment

Gardening, Polivalente.

≥ 0.32

≥ 0.28

≥ 0.18

> 0.13

SRC (SRA+SRB)

Sole 81 PU - PU

0.52

0.48

0.23

0.18

SRC

SRA

DETERGENT

SRB

Antistatic

WEL

Wire Electricity Discharge

Strip with 4 filaments

of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Building, Finishing-off building, Farming and

PU Dual-Density SRC passed

EN ISO 20345:2011

Availability in stock

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

Removable Insole



The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.

Protection Elements





Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.

Type Ankle boot Upper Full Grain leather Hydrotech Greased Nubuk Leather Hydrotech Fabric of High Tenacity

Lining 3D Air circulation 320 gr.

DUALMICRO Antislip Lining

Removable Insole **Blowfit**

PU Dual-Density SRC passed

Sole

Toe Cap Anti-Perforation

Zero(4K)-Antiperforation 38-48

Weight gr.

680

Features

Size



ZERO(k)



C.T.C. - Composite Toe Cap















Symbols





Via A. Einstein, 6 - 35020 Casalserugo (PD) - ITALY - Tel. +39 049 8740771 - Fax. +39 049 8741376 - mail info@maspica.it - www.sixton.it

Technical Data Sheet 18 May 2017